



REVISIONS				
ZONE	SYM	DESCRIPTION	DATE	APPROVED
-		INITIAL RELEASE	7-18-17	MRG

LOGIC TABLE

TTL	RF ON
3	2 1 J1 →
0	0 0 J2
0	0 1 J3
0	1 0 J4
0	1 1 J5
1	X X ALL OFF

PIN NUMBER	FUNCTION
1	+5VDC
2	+12VDC
3	N/C
4	TTL2
5	TTL3
6	GROUND
7	+400VDC
8	-12VDC
9	TTL1

CAUTION: 1. APPLY +400 V LAST REMOVE FIRST
2. HEAT SINK REQUIRED

NOTES:
1. FINISH: WASH PRIMER PER DDD-P-15328
PRIMER PER MIL-P-23377
PAINT PER MIL-C-22750
COLOR BLUE
2. MARKING: BLACK EPOXY INK .12 HIGH CHARACTERS
PER MIL-STD-130

M83513/03-A03C
IAW MIL-C-83513
CLASS M, TYPE II

CAUTION
STATIC SENSITIVE MATERIAL
ALL HANDLING/INSPECTION TO BE PERFORMED
ONLY AT APPROVED WORK STATIONS

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF RH LABS AND SHALL NOT BE REPRODUCED OR COPIED OR USED IN PART AS THE BASIS FOR THE MANUFACTURE OR SALE OF ITEMS WITHOUT WRITTEN PERMISSION

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON FINISHES ANGLES: 1/2" FRACTIONS: 1/64 3 PLACE DECIMALS: ±.005 2 PLACE DECIMALS: ±.02 1 PLACE DECIMALS: ±.1 FILLETS: .005R MAX REMOVE BURRS AND SHARP EDGES TO .005 MAX. R OR CHAMFER	DRAFT MRG DATE 7-18-17
CHKD MRG DATE 7-18-17	
PRDD	
ENGR	
QA	

TITLE OUTLINE SP4T SWITCH		
SIZE B	CAGE CODE 1UJ73	DWG NO 140-F208
SCALE 2/1	SHEET 1 OF 1	