


NOTES:

1. MATERIAL: KOVAR PER MIL-I-23011, CLASS 1
2. FINISH: GOLD PLATE PER MIL-G-45204, TYPE III



REVISIONS		
SYM	DESCRIPTION	DATE APPROVED

SPECIFICATIONS

RF INPUT FREQUENCY (GHz):	2.0 TO 8.0 GHz
OPEN CIRCUIT SENSITIVITY:	2000 mV/mW MIN.
INPUT POWER RANGE:	TSS TO +10.0 dBm
OUTPUT VOLTAGE FLATNESS vs FREQUENCY:	±0.6 dB
TSS:	-52 dBm MIN.
NOMINAL VIDEO CAPACITANCE:	20 pF
MAX. CW RF INPUT:	+23 dBm
OPERATING TEMP. RANGE:	-55°C TO +125°C
STORAGE TEMP. RANGE:	-65°C TO +150°C

SPECIFICATION NOTES:

1. SENSITIVITY MEASURED AT -20dBm, LOAD = 30K OHMS
2. OUTPUT POLARITY IS NEGATIVE. FOR POSITIVE OUTPUT ADD "P" TO PART NUMBER.
3. TSS BASED ON 2 MHz VIDEO BANDWIDTH AND 2 dB AMPLIFIER NF.

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF RH LABS AND SHALL NOT BE REPRODUCED OR COPIED OR USED IN PART AS THE BASIS FOR THE MANUFACTURE OR SALE OF ITEM(S) WITHOUT WRITTEN PERMISSION							
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON FINISH: RMS63 ANGLES: ±1/2° FRACTIONS: ±1/64 3 PLACE DECIMALS: .005 2 PLACE DECIMALS: .01 1 PLACE DECIMALS: .1 FILLETS: .005R MAX REMOVE BURRS AND SHARP EDGES TO .005 MAX. R OR CHAMFER	DRAFT	R.A.J.	DATE	8/27/02	TITLE	ZERO BIAS DETECTOR	
	CHKD				SIZE	CAGE CODE	DWG NO
	PROD				A	1UJ73	OD930-D104
	ENGR	R.A.J.		8/27/02	SCALE	4:1	SHEET 1 OF 1
	QA						