



**NOTES:**

1. MATERIAL: KOVAR PER MIL-I-23011, CLASS 1
2. FINISH: GOLD PLATE PER MIL-G-45204, TYPE III



REVISIONS			
SYM	DESCRIPTION	DATE	APPROVED

**SPECIFICATIONS**

RF INPUT FREQUENCY (GHz):	8.0 TO 18.0 GHz
OPEN CIRCUIT SENSITIVITY:	1800 mV/mW MIN.
INPUT POWER RANGE:	TSS TO +10.0 dBm
OUTPUT VOLTAGE FLATNESS vs FREQUENCY:	±0.7 dB
TSS:	-52 dBm MIN.
NOMINAL VIDEO CAPACITANCE:	15 pF
MAX. CW RF INPUT:	+23 dBm
OPERATING TEMP. RANGE:	-55°C TO +125°C
STORAGE TEMP. RANGE:	-65°C TO +150°C

**SPECIFICATION NOTES:**

1. SENSITIVITY MEASURED AT -20dBm, LOAD = 30K OHMS
2. OUPUT POLARITY IS NEGATIVE. FOR POSITIVE OUTPUT ADD "P" TO PART NUMBER.
3. TSS BASED ON 2 MHz VIDEO BANDWIDTH AND 2 dB AMPLIFIER NF.

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF RH LABS AND SHALL NOT BE REPRODUCED OR COPIED OR USED IN PART AS THE BASIS FOR THE MANUFACTURE OR SALE OF ITEM(S) WITHOUT WRITTEN PERMISSION



UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON FINISH: RMS63 ANGLES: ±1/2° FRACTIONS: ±1/64 3 PLACE DECIMALS: ± .005 2 PLACE DECIMALS: ± .01 1 PLACE DECIMALS: ± .1 FILLET: .005R MAX REMOVE BURRS AND SHARP EDGES TO .005 MAX. R OR CHAMFER	DRAFT	R.A.J.	DATE	TITLE		
	CHKD		8/27/02	ZERO BIAS DETECTOR		
	PROD			SIZE	CAGE CODE	DWG NO
	ENGR	R.A.J.	8/27/02	A	1UJ73	OD930-D106
QA			SCALE	4:1	SHEET 1 OF 1	