



REVISIONS				
ZONE	SYM	DESCRIPTION	DATE	APPROVED

SPECIFICATIONS
 FREQUENCY RANGE: 0.5-4.0 GHz
 INSERTION LOSS: 1.4 dB MAX
 ISOLATION: 60 dB MIN
 VSWR: 2.0:1
 SWITCHING SPEED: 25 NANO SEC MAX
 BIAS: +5 VDC
 -12 VDC
 POWER HANDLING: 1 WATT CW

LOGIC: TTL COMPATIBLE

A0	A1	A2	CONDITION
1	0	0	LOW LOSS J0-J1
0	1	0	LOW LOSS J0-J3
0	0	1	LOW LOSS J0-J5

- NOTES:
- FINISH: WASH PRIMER PER DOD-P-15328D
 PRIMER PER MIL-P-23377D
 PAINT PER MIL-C-22750
 COLOR :BLUE
 MOUNTING PLATE SHALL BE IRRIDITE PER MIL-5541C,
 CLASS 3
 - MARKING: BLACK EPOXY INK .06 HIGH CHARACTERS EXCEPT
 SERIAL NUMBER AND DATE CODE .06 HIGH
 PER MIL-STD- 130

<small>THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF RH LABS AND SHALL NOT BE REPRODUCED OR COPIED OR USED IN PART AS THE BASIS FOR THE MANUFACTURE OR SALE OF ITEM(S) WITHOUT WRITTEN PERMISSION</small>				
<small>UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON FINISH RMS63 ANGLES-1/2° FRACTIONS-1/64 3 PLACE DECIMALS: ±.010 2 PLACE DECIMALS: ±.02 1 PLACE DECIMALS: ±.1 FILLETS: .008R MAX REMOVE BURRS AND SHARP EDGES TO .005 MAX. R OR CHAMFER</small>			TITLE OUTLINE SP3T SWITCH	
DRAFT	MRG	DATE	SIZE	CAGE CODE
		7-22-02	B	1UJ73
CHKD			DWG NO	130-F201
PRD			SCALE	2/1
ENGR				SHEET 1 OF 1
QA				



One Tanguay Avenue
 Nashua, New Hampshire 03063-1711
 Phone: 603-459-5900 • Fax: 603-459-5901
 Email: Sales@RH-Labs.com