



REVISIONS				
ZONE	SYM	DESCRIPTION	DATE	APPROVED

SPECIFICATIONS
 FREQUENCY RANGE: 2-18 GHz
 INSERTION LOSS: 2.5 dB MAX
 ISOLATION: 60 dB MIN
 VSWR: 2.0:1
 SWITCHING SPEED: 25 NANO SEC MAX
 BIAS: +5 VDC
 -12 VDC
 LOGIC: "0"= LOW LOSS
 "1"= ISOLATION
 POWER HANDLING: 1 WATT CW

- NOTES:**
- FINISH: WASH PRIMER PER DDD-P-15328D
 PRIMER PER MIL-P-23377D
 PAINT PER MIL-C-22750
 COLOR :BLUE
 - MARKING: BLACK EPOXY INK .04 HIGH CHARACTERS EXCEPT
 SERIAL NUMBER AND DATE CODE .06 HIGH
 PER MIL-STD- 130

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF RH LABS AND SHALL NOT BE REPRODUCED OR COPIED OR USED IN PART AS THE BASIS FOR THE MANUFACTURE OR SALE OF ITEMS WITHOUT WRITTEN PERMISSION

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON FINISH: RMS63 ANGLES: 1/2" FRACTIONS: ±1/64 3 PLACE DECIMALS: ±.010 2 PLACE DECIMALS: ±.02 1 PLACE DECIMALS: ±.1 FILLET: .005R MAX REMOVE BURRS AND SHARP EDGES TO .005 MAX. R OR CHAMFER	DRAFT MRG	DATE 7-22-02
CHKD		
PRD		
ENGR		
QA		

TITLE OUTLINE SPDT SWITCH		
SIZE B	CAGE CODE 1UJ73	DWG NO 120-F200
SCALE 2/1	SHEET 1 OF 1	



One Tanguay Avenue
 Nashua, New Hampshire 03063-1711
 Phone: 603-459-5900 • Fax: 603-459-5901
 Email: Sales@RH-Labs.com