



REVISIONS				
ZONE	SYM	DESCRIPTION	DATE	APPROVED

SPECIFICATIONS

FREQUENCY RANGE:	0.5-4.0 GHz
INSERTION LOSS:	1.4 dB MAX
ISOLATION:	60 dB MIN
VSWR:	2.0:1
SWITCHING SPEED:	25 NANO SEC MAX
BIAS:	+5 VDC -12 VDC
LOGIC:	"0"= LOW LOSS "1"= ISOLATION
POWER HANDLING:	1 WATT CW

- NOTES:
- FINISH: WASH PRIMER PER DOD-P-15328D  
PRIMER PER MIL-P-23377D  
PAINT PER MIL-C-22750  
COLOR :BLUE
  - MARKING: BLACK EPOXY INK .04 HIGH CHARACTERS EXCEPT  
SERIAL NUMBER AND DATE CODE .06 HIGH  
PER MIL-STD- 130

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF RH LABS AND SHALL NOT BE REPRODUCED OR COPIED OR USED IN PART AS THE BASIS FOR THE MANUFACTURE OR SALE OF ITEMS) WITHOUT WRITTEN PERMISSION

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES  
TOLERANCES: ON FINISH RMS63  
ANGLES: ±1/2° FRACTIONS: ±1/64  
3 PLACE DECIMALS: ±.010  
2 PLACE DECIMALS: ±.02  
1 PLACE DECIMALS: ±.1  
FILLETS: .005R MAX  
REMOVE BURRS AND SHARP EDGES TO .005 MAX. R OR CHAMFER

DRAFT	MRG	DATE
CHKD		7-22-02
PRD		
ENGR		
QA		

TITLE			OUTLINE	
			SPDT SWITCH	
SIZE	CAGE CODE	DWG NO		
B	1UJ73	120-F201		
SCALE	2/1		SHEET	1 OF 1



One Tanguay Avenue  
 Nashua, New Hampshire 03063-1711  
 Phone: 603-459-5900 • Fax: 603-459-5901  
 Email: Sales@RH-Labs.com